



Wondermask® PL Latex

Peelable Solder Mask 2218

Introduction

Wondermask® PL Latex is a temporary, peelable solder mask comprised of a thixotropic, natural acrylic latex designed to withstand fluxing, wave soldering, and cleaning operations. Wondermask® PL Latex is rapid drying and has excellent peel strength. Cured mask can be used in water or solvent systems and in masking for conformal coatings. Excellent heat stability allows for prolonged exposure to high temperatures, without product degradation. This product may be used in most common forms of mask applications such as robotic, pneumatic, hand applied, or template screening (not recommended for silk screening).

Features / Benefits

- Peelable
- Natural Latex
- Lead Free Compatible
- Ammoniated
- Quick Drying

Chemical Components

Latex		90-99%
Ammonia.....	(7664-41-7)	<.3%
Zinc Oxide.....	(1314-13-2)	<.2%
Zinc Dibutyl Dithiocarbamate.....	(136-23-2)	<.4%

Application	Cure Type	Cure Time	Removal	Viscosity	Suggested Thickness	Thinner
Template/Hand/ Pneumatic/ Robotic	Thermal	1 hr. Ambient 20-30 min @65°C	Peel off. Dried mask is not soluble in liquids	9,000-15,000 cps	15 mils	D.I. Water

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

Wondermask® PL Latex 2218 may be ordered in the following container sizes:

2218-8SQ	8 Ounce Squeeze Bottle
2218-G	1 Gallon in Plastic
2218-5G	5 Gallons in Plastic

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America
Tech Spray L.P.
P.O. Box 949
Amarillo, TX 79105
800-858-4043
email: tsales@techspray.com

Europe
Techspray International
UNIT 4, 44/46 Bunyan Road, Kempston
Bedford MK42 8HL United Kingdom
+44 (0) 1234 855443
email: tseurope@techspray.com

Countries Outside US
Call to locate a distributor
in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P.
P.O. Box 949
Amarillo, TX 79105
www.techspray.com

[English MSDS](#)
[French MSDS](#)
[German MSDS](#)
[Italian MSDS](#)
[Spanish MSDS](#)

